JOWAT 195.40

## **Crosslinking Agent**

**Basis:** Emulsifiable, modified polyisocyanate.

**Technical Data:** Viscosity (mPas): approx. 1,300 (Brookfield)
Density (g/cm³): approx. 1.14 (9.5) lbs./gal)

NCO content (%): approx. 20 clear

**Characteristics:** Increases the resistance of a dispersion adhesive to moisture; also increases the adhesive properties.

**Applications:** Increases water resistance and adhesion when mixed with various dispersion adhesives.

**Directions** Optimum processing approx. 4-8 hours at 3-5% (depending on the type of dispersion)

Please refer to the individual data sheets for the various emulsion glues. Containers which are used to pre-mix Jowat 195.40 may not be tightly closed (they may burst due to formation of carbon dioxide.

Tested according to Jowat test methods. Customer trials are recommended.

Cleaning: Machines and equipment may be cleaned after use with warm or cold water, using Jowat Cleaner

Concentrate 192.40. Parts only soiled with the crosslinking agent may be cleaned with Jowat Thinner

401.40/402.30. Cured adhesive compound can only be cleaned mechanically.

**Storage:** May be stored for six (6) months after date of delivery ex production site in properly closed original

containers, cool and dry (15-25°C). Keep containers well-closed. Keep the containers tightly sealed and

protect against humidity.

Packaging: Unit size on request.

**Marking:** Consult Material Safety Data Sheet for further information.

**Date Revised:** March 2005 (S)

The information contained in this leaflet is based upon our practical experience and the results of tests in our laboratory. The information contained represents average values under our test conditions. Although our testing is constantly being revised to represent the latest conditions, the information provided in this leaflet and by our free technical information service should be used only as a guide, but cannot be relied upon as a guaranty of performance or results. We strongly recommend that any user of our products conduct its own testing.

Adhesives
Jowat Corporation
Randolph Industrial Park
P.O. Box 1368
High Point, NC 27261

Phone: (800) 322-GLUE (4583) (336) 434-9000 Fax: (336) 434-9019 Website: www.jowat.com

Email: info@jowat.com