## JOWATHERM Packaging Hot Melt

Basis:	Ethylene - Vinyl Acetate (EVA)
Technical Data:	Viscosity (mPas/cPs):approx. 2,500 at 300°F (149°C) Brookfield-Thermosel approx. 1,400 at 325°F (163°C) approx. 1,000 at 350°F (177°C) approx. 700 at 375°F (191°C)Density (g/ml):approx. 95 (8.0 lbs./gal) approx. 230°F (110°C) Ring & Ball Color:Color:Yellow - translucent
Characteristics:	Low viscosity hot melt that is extremely fast setting with good color and heat stability in the melt. All raw materials used in the manufacturing of 259.10 are approved according to FDA guidelines 175.105 for food packaging.
Applications:	Especially for high speed packaging lines; tray forming, box closing, wrap around and similar applications.
Directions for use:	Application Temp:325-375°F (162-191°C) in the meltOpen Time at 350°F:approx. 8-9 secondsSet Time at 350°F:approx. 1-2 secondsTested according to Jowat test methods. Customer trials are recommended.
Cleaning:	Preliminary cleaning while hot by scraping with a spatula; when cold with Jowat Cleaner 401.20.
Storage:	At least 3 years from the date of manufacture in dry and cool (15-25°C/58-76°F) conditions according to our experience.
Packaging:	In cartons of 50 lbs. net.
Marking:	None. We recommend drawing off any vapors which may form. Consult Material Safety Data Sheet.
Date Revised:	June 2005 (S)

The information contained in this leaflet is based upon our practical experience and the results of tests in our laboratory. The information contained represents average values under our test conditions. Although our testing is constantly being revised to represent the latest conditions, the information provided in this leaflet and by our free technical information service should be used only as a guide, but cannot be relied upon as a guaranty of performance or results. We strongly recommend that any user of our products conduct its own testing.

SEE THE BACK OF THIS PAGE FOR ADDITIONAL IMPORTANT INFORMATION.

Jowat Corporation Randolph Industrial Park P.O. Box 1368 High Point, NC 27261 Phone: (800) 322-GLUE (4583) (336) 434-9000 Fax: (336) 434-9019 Website: www.jowat.com Email: info@jowat.com

259.10